

Motorola Canopy
2.4 GHz Advantage AP



Canopy Part Number	2450APBC
Description	2.4 GHz Advantage AP
Signaling Rate	20 Mbps Maximum
Typical LOS Range	5 Mi (8 km)
Typical Aggregate Useful Throughput	14 Mbps Maximum
Frequency range of band	ISM 2400-2483.5 MHz
Non-overlapping Channels	3
Channel Width	20 MHz
Modulation Type	High Index 2-level and 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	every 2.5 MHz
Encryption	DES capable
Latency	5 - 7 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-86 dBm
Antenna Gain (dB)	8 dB
EIRP (dB)	Adjustable
Equivalent Isotropic Radiated Power (EIRP)	Adjustable from 10 mW to 2.0 W
DC Power (typical)	0.3 A @ 24 VDC = 7.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, Azimuth and Elevation
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplexing/Time Division Multiple Access (TDD/TDMA)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
FCC ID	ABZ89FC5808
Industry Canada Certification Number	109W-2400