

Non-line-of-sight :: 900 MHz

The AW-D2-900 replaces costly cables and trenching with a non-line-of-sight, wireless network camera housing that enables remote network cameras. AvaLAN's products offer the ideal combination of price, penetrating range, data rate, security, interference avoidance, Quality of Service, and ease-of-use.



AW-D2-900 Kit

Integrated 900 MHz wireless dome housing for PTZ network cameras. Kit includes:

- › (1) Dotworkz D2 outdoor dome housing with heater/blower
- › (1) AW900x outdoor radio
- › (2) 120 VAC to 24 VAC/40 Va transformers
- › (2) AW2 2.5 dBi omni-directional antennae
- › (1) 120 VAC to 12 VDC power adapter
- › (1) Power over Ethernet injector

Features

- › High RF output power and exceptional receive sensitivity provide ultra-long-range wireless IP digital video delivery up to 40 miles line-of-sight or 10 walls/grove of trees for non-line-of-sight applications
- › Does not interfere with Wi-Fi networks
- › 128 bit encrypted with dynamic private keys
- › Highest Quality of Service (QoS) available — synchronous point-to-point protocol enables IP video applications that require low data latency and jitter
- › Gł a d'Y' d'i ['UbX' d'Umí 'dfY!Vzbu[i fYX' Ug'a UHWYX' dUJfg'k]h' bc'i gYf' programming required
- › 12 non-overlapping channels with frequency agility to avoid interference
- › Operates in the 902-928 MHz band and does not require a license to operate or install in the USA or Canada

For a list of network cameras supported, please visit:
<http://www.avalanwireless.com/NetworkCameras.htm>



